

Mold NO. 1.02.81480


Part NO. HK-260@10-40X80-5050-00-1g-28_PC
HK-260@10-40X80-5050-00-1g-28_PMMA

Material PC/PMMA

Efficiency 90% (PC) /93% (PMMA)

LED 3535/5050 LED

Light distribution type TYPE I 40°X80°



Height

7m

Mode

Top cloth lamp

Corridor
uniformity

0.9



Mold NO.	1.02.81420
Part NO.	HK-260@08-150X80-5050-#0-1g-28_PC HK-260@08-150X80-5050-#0-1g-28_PMMA

Material	PC/PMMA
----------	---------

Efficiency	90% (PC) /93% (PMMA)
------------	----------------------

LED	3535/5050 LED
-----	---------------

Light distribution type	TYPE II_M 150°X80°
-------------------------	--------------------



Proportion	4.5:1
Road width	7m (2 lanes)
Mode	Unilateral
Lighting type	ME3a

Mold NO. 1.02.81498

Part NO.

HK-260@10-65X152-5050-#0-1g-28_PC
HK-260@10-65X152-5050-#0-1g-28_PMMA

Material

PC/PMMA

Efficiency



90% (PC) / 93% (PMMA)

LED

3535/5050 LED

Light distribution
type

TYPE III 65°X152°



Proportion

4:1

Road width

22.5m (6 lanes)

Mode

Bidirectional
symmetry

Lighting type

ME3a

Mold NO.

1.02.81492

Part NO.

HK-260@10-30X140-5050-#0-1g-28_PC
HK-260@10-30X140-5050-#0-1g-28_PMMA

Material

PC/PMMA

Efficiency



90% (PC) /93% (PMMA)

LED

3535/5050 LED

Light distribution
type

TYPE IV 30°X140°



Height

11m

Mode

Four corner
arrangement lights

Court uniformity

0.9

Mold NO. 1.02.81465




Part NO. HK-260@08-140-5050-#0-1g-28_PC
HK-260@08-140-5050-#0-1g-28_PMMA

Material PC/PMMA

Efficiency 90% (PC) /93% (PMMA)

LED 3535/5050 LED

Light distribution type TYPE V 140°



Height	25m
Mode	Center layout light
Square uniformity	0.8